



## TECHNICAL SHEET

valid from 1.12.2011

review .....

<b>PRODUCT NAME:</b>	<b>SCÉNIC SPRING</b>
<b>APPLICATION:</b>	<b>LANDSCAPING</b>
<b>MATERIAL:</b>	<b>PILE:</b> PE monofilament – mild lens profil (straight + texturized)
	<b>PRIM. BACKING:</b> 100% PP
	<b>SECONDARY BACKING:</b> SBR Latex
<b>GAUGE:</b>	3/8"
<b>COLOR:</b>	tricolor green, sand (field green + spring green/ olive green + sand)

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	14.200/16	± 5%
Pile width	[mm]	0,9	± 10%
Pile thickness	[µm]	170	± 10%
Pile weight per unit area	[g/m <sup>2</sup> ]	2.144	± 10%
Stitch rate per 10 cm (length)	[-/ 10 cm]	18	± 1
Number of tufts / m <sup>2</sup>	[-/m <sup>2</sup> ]	18.898	± 5%
Number of piles / m <sup>2</sup>	[-/m <sup>2</sup> ]	604.736	± 5%
Pile height	[mm]	28	± 10%
Weight primary backing	[g/m <sup>2</sup> ]	172	± 10%
Weight secondary backing	[g/m <sup>2</sup> ]	700	± 10%
Total weight	[g/m <sup>2</sup> ]	3.016	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,00; 2,00	± 0,02

### COMMENTS:

**Recommended infill:** non filled

Any supplementary information and certificates are available upon request at our sales department. According to the Directive 76/ 769 this product does not contain any dangerous substances.

**FEXIDAL BVBA** - Leon Bekaertlaan 36, 9880 Aalter, Tel +32/9-325.07.55

Fax +32/9-325.06.55 [www.rubbervloer.be](http://www.rubbervloer.be) - [info@rubbervloer.be](mailto:info@rubbervloer.be)