



TECHNICAL SHEET

valid from 1.3.2016

review

PRODUCT NAME:	GAMIN 20/150
APPLICATION:	MULTISPORT, PLAYGROUNDS
MATERIAL:	PILE: PE monofilament (texturized)
	PRIMARY BACKING: 100% PP
	SECONDARY BACKING: SBR Latex
GAUGE:	3/8"
COLOR:	olive green

PROPERTIES	UNIT	TYPICAL VALUE	TOLERATION
Pile fineness	[dtex]	11.500/8	± 10%
Pile width	[mm]	1	± 10%
Pile thickness	[µm]	180	± 10%
Pile weight per unit area	[g/m ²]	887	± 10%
Stitch rate per 10 cm (length)	[-/10 cm]	15	± 10%
Number of tufts/m ²	[-/m ²]	15.748	± 10%
Number of piles/m ²	[-/m ²]	251.968	± 5%
Pile height	[mm]	20	± 5%
Weight primary backing	[g/m ²]	170	± 10%
Weight secondary backing	[g/m ²]	950	± 10%
Total weight	[g/m ²]	2.007	± 10%
Turf withdrawal force	[N]	> 30	
UV stabilisation (QUV – lamp A)	[h]	3.000	
Color fastness – gray scale	Scale	≥ 4	
Stand. roll width	[m]	4,02	± 0,02

COMMENTS:

Any supplementary information and certificates are available upon request at our sales department. According to the Regulation (EC) No 1907/2006 (REACH), this product does not contain any dangerous substances.

JUTA a.s. reserves the right to amend the technical specifications of the above mentioned product. The delivered product may slightly differ from these data. JUTA a.s. guarantees the technical quality of the product.

FEXIDAL BVBA - Leon Bekaertlaan 36, 9880 Aalter, Tel +32/9-325.07.55

Fax +32/9-325.06.55 www.rubbervloer.be - info@rubbervloer.be